# SPA-QUIP

# **SPA POWER 800**


The Spa Power 800 is the mid ranged automatic temperature controlled spa heater/controller for spa pools. Featuring two heating element sizes and AMP outlet sockets to control pumps blowers and ozonators. Touch pad available has alpha numerical LCD display and muilticoloured backlighting for night use.

# **Features**

- -Available in two element wattages 2kW, 3kW
- -2 x Single speed pumps or 1 x two speed pump control for pump up to 2100 Watts
- -24Hr circulation pump control
- -Single speed blower or extra single speed pump
- -Variable speed blower (SPVSB) control
- -Pool temperature control using either an "In pool" or "In heater" sensor
- -Touch pad controllable sleep time clock
- -Adjustable filtration control
- -Maintenance Timers
- -Touch pad child lock
- -Multilingual touch pad display, selectable languages English, French
- & German
- -Super hard, non stick, 250°C element coating
- -Safety thermal cutout
- -Optical water sensor
- -Spa Power Variable colour light (SPVCL) providing control of up to 4 lights with the following effects:
- 13 colours and six types of colour merging effects.







At night fall the Spa Power 800 touch pad really comes to life where you can have a dazzling led light display or a sultry relaxing glow. An absolute necessity for all.











# **SPA POWER 800**

### **Approvals**

Matches the Spa Power range of equipment offering safety, EMC and immunity approvals to EN standards, making it suitable for sale in markets such as Europe, Australia and New Zealand.

> 2 x 3-4 button t/pad 4 x 1-2 button t/pad

3 x 1 button t/pad

In heater and In pool

3 mtr std or 10mtr

up to 4 std

up to 10

# **Specifications**

SP800 dimensions 360 x 220 x 95 Heater tube pipe diameter 50mm Heater pressure, max (head of water) 300kPa (31m) Temp - max controlled 41.5°C Temp - thermal cut out 50°C +/- 3°C Temp - max ambient 40°C Mains cord length Not Fitted

Pool side touch pad - face 172mm x 89mm x 5mm Pool side touch pad - body 135mm x 65mm x 26mm

(Pool side touch pad available in oval and rectangle shapes)

Recommended touch pad cut out See diagram Number of touch pads 1 std, 2 optional

Number of remote touch pads when connected to

switch expander pcb (optional extra)

Number of LED lights Total number of LED lights possible when connected to

light expander pcb (optional extra) Temperature sensors Switch lead length

Supply Requirements (Max total loading)

All models of SP800

220 - 240V. AC. 50-60Hz (40A max total load)

Max outlet loading

Pump 1A - Single speed or two speed 220 - 240V, AC, 50-60Hz, 10A Pump 1B - Single speed 220 - 240V, AC, 50-60Hz, 10A Aux (can be used for extra pump, blower) 220 - 240V, AC, 50-60Hz, 10A Spa Power Variable Speed Blower (SPVSB) 220 - 240V, AC, 50-60Hz, 7.5A 220 - 240V, AC, 50-60Hz, 2.5A Circ pump 220 - 240V, AC, 50-60Hz, 2A Ozone

70mm

Oval and rectangle touch pad hole cutout 2 x holes cut with 65mm hole saw at 70mm centres.

# **Purchasing Information**

Q800-20 Spa Power 800, 2kW heating element

Q800AU-20 Spa Power 800, 2kW heating element & AS/NZ 15 Amp Cordset

Q800-30 Spa Power 800, 3kW heating element Spa Power 800 oval touch pad with 3mtr lead Q70068 Spa Power 800 oval touch pad with 10mtr lead Q70068-10 Spa Power 800 oval touch pad overlay Q616013

Spa Power 800 rectangle touch pad with 3mtr lead Q70069 Q70069-10 Spa Power 800 rectangle touch pad with 10mtr lead Spa Power 800 rectangle touch pad overlay Q616014

Spa Power Equipment manufactured in New Zealand by Spa-Quip Ltd

.iotl 2 Rothwell Avenue, North Harbour Industrial Park, Auckland, NZ www.spa-quip.co.nz



