SPACE SPACE SPEED BLOWER (SPVSB)

The cleverly designed SPVSB has been produced to accompany the latest Spa Power range of controllers or to be used as a stand alone unit. It contains all the required speed control circuitry and simply plugs into a controller or it's very own pool side touch pad. When used with a controller the SPVSB is controlled via the controller's pool side touch pad. In either configuration the user can control the air flow in the pool simply by pressing a button.




SPVSB's are available with or without a fitted power supply. Those without a power supply are intended for use only with a Spa Power controller to help minimise overall system cost. Whereas those with a power supply can be used either with a controller or in the stand alone configuration.

SPVSB Single button touchpad

A small touch pad designed to replace an air switch. It offers high, medium and oscillating speed control of the SPVSB and features a tri colour LED to denote the current speed setting.





SPVSB Three button touchpad

A standard size touch pad featuring three buttons to select high, medium,and oscillating speed control of the SPVSB and additional fine adjustment. It includes two standard LEDs and a tri colour LED for easy operation.







Approvals

Matches the Spa Power range of equipment offering safety, EMC and immunity approvals to EN standards, making it suitable for sale in markets such as Europe, Australia and New Zealand.

Specifications

SPVSB dimensions Outlet pipe diameter Max back pressure for low setting Flow rate - high setting (open discharge) Flow rate - low setting (open discharge) Temp - max ambiant Control lead length	270mm x 170mm x 170mm 40mm 1psi (700mm H20) 60l/s 46l/s 40°C 84mm 2.5m
Three button Pool side touchpad - face (rectangle) Pool side touchpad - body (rectangle) Recommended switch hole (rectangle) Switch lead length	118mm x 65mm x 6mm A 92mm x 40mm x 22mm Rectangle switch hole cutout 92mm x 40mm x 22mm 32mm See diagram A 0.5m (plus SPVSB control lead)
Single button Switch dimensions - face Switch dimensions - body Recommened switch hole Switch lead length	48mm dia 32mm dia 35mm dia 0.5m (plus SPVSB control lead)

Purchasing Informati	ion
Part No	Product
Q5602-AMP	SPVSB without power supply with 3mtr AMP lead
Q5602-IEC	SPVSB without power supply *(type of mains lead optional)(see below for options)
Q5602-JJB6	SPVSB without power supply with 2mtr blower JJ lead
Q5603-IEC	SPVSB with power supply *(type of mains lead optional)(see below for options)
Q5603-JJB6	SPVSB with power supply with 2mtr blower JJ lead
Q71089	SPVSB single button touch pad
Q71088	SPVSB three button touchpad
*Mains lead Options	For IEC Socket Blower Models
0912011	IEC to Cat 38 cable 2mtr

IEC to Cat 38 cable 2mtr IEC to AMP cable 3mtr 6-IEC IEC to Blower JJ cable 2 mtr

Spa Power Equipment manufactured in New Zealand by Spa-Quip Ltd

2 Rothwell Avenue, North Harbour Industrial Park, Auckland, NZ www.spa-quip.co.nz



