SPA-QUIP SPA POWER VARIABLE SPEED BLOWER (SPVSB)

The cleverly designed SPVSB has been produced to accompany the latest Spa Power range of controllers or to be used as a stand alone unit. It contains all the required speed control circuitry and simply plugs into a controller or it's very own pool side touch pad. When used with a controller the SPVSB is controlled via the controller's pool side touch pad. In either configuration the user can control the air flow in the pool simply by pressing a button.




SPVSB's are available with or without a fitted power supply. Those without a power supply are intended for use only with a Spa Power controller to help minimise overall system cost. Whereas those with a power supply can be used either with a controller or in the stand alone configuration.

SPVSB Single button touchpad

A small touch pad designed to replace an air switch. It offers high, medium and oscillating speed control of the SPVSB and features a tri colour LED to denote the current speed setting.





SPVSB Three button touchpad

A standard size touch pad featuring three buttons to select high, medium, and oscillating speed control of the SPVSB and additional fine adjustment. It includes two standard LEDs and a tri colour LED for easy operation.











Approvals

Matches the Spa Power range of equipment offering safety, EMC and immunity approvals to EN standards, making it suitable for sale in markets such as Europe, Australia and New Zealand.

Specifications

| • | | | |
|---|---|---|--|
| SPVSB dimensions Outlet pipe diameter Max back pressure for low settin Flow rate - high setting (open dis Flow rate - low setting (open disc Temp - max ambiant Control lead length | scharge) | 270mm x 170mm x 170mm 40mm 1psi (700mm H20) 60l/s 46l/s 40°C 2.5m | 84mm |
| Three button Pool side touchpad - face (recta Pool side touchpad - body (recta Recommended switch hole (rect Switch lead length | ingle) | 118mm x 65mm x 6mm A 92mm x 40mm x 22mm See diagram A 0.5m (plus SPVSB control lead) | Rectangle switch hole cutout 94mm x 42mm 10mm dia hole x 4 |
| Single button Switch dimensions - face Switch dimensions - body Recommened switch hole Switch lead length | | 48mm dia 32mm dia 35mm dia 0.5m (plus SPVSB control lead) | |
| Purchasing Information Part No Q5602-AMP Q5602-IEC Q5602-JJB6 | ProductSPVSB without power supplywith 3mtr AMP leadSPVSB without power supply*(type of mains lead optional)(see below for options)SPVSB without power supplywith 2mtr blower JJ lead | | |
| Q5603-IEC Q5603-JJB6 Q71089 Q71088 | SPVSB with power supply *(type of mains lead optional)(see below for options) SPVSB with power supply with 2mtr blower JJ lead SPVSB single button touch pad SPVSB three button touchpad | | |

*Mains lead Options For IEC Socket Blower Models

| Q912011 | IEC to Cat 38 cable 2mtr |
|---------------|------------------------------|
| Q912025 | IEC to AMP cable 3mtr |
| Q912021-6-IEC | IEC to Blower JJ cable 2 mtr |

Spa Power Equipment manufactured in New Zealand by Spa-Quip Ltd

2 Rothwell Avenue, North Harbour Industrial Park, Auckland, NZ www.spa-quip.co.nz





SPA EQUIPMENT

